


Name _____ Date _____ Truck / City _____ Event _____

Front Suspension



Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128(Std.) UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

AL. Steering Support: None UMW724

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: _____ mm

UMW701 Aluminum ST Plate UMW702 Aluminum Clank Arm

AXLE SPACER: Out _____ mm In _____ mm

Wheel Hub: UM569 / Std UM506

Bump Steer Spacer: _____ mm

AXLE HEIGHT SPACER: _____ mm _____ mm

Caster: 25° 30°

Caster Block: 0.5 0° 1.0 2° None 4°

Caster Block Position: IN (wide/Std) OUT (Narrow)

Front Bulkhead Weight Placement:

None

Bulkhead Inside _____ oz _____ g

On the skid plate _____ oz _____ g * 1oz=28g

Comments: _____

Wheelbase: F: _____ mm R: _____ mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128(Std.)

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Universal Swing Shaft: _____

Camber: _____ °

Wheelbase: F: _____ mm R: _____ mm

Sway Bar: None _____ mm

Drive Hub : 4mm (TFW113) 4.5mm (LAW30GM/Std.) 5.2mm (UMW523)

Rear Hub Carrier : 0° Type-B (UM519) 0° Type-B2 (UM519-2) 0° Alu (UMW704-0) 0.5° Alu (UMW704-05) 1° Alu (UMW704-1)

AXLE SPACER: Out _____ mm In _____ mm

Lower Sus. Holder: Normal Narrow RF Wide RF2 Option UMW511GM (RF/Alu)

RR: _____

Mid: _____

Motor Position Rear Motor Midship Motor

Diff. Gear Diff. # _____ Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top type:	<input type="checkbox"/> Alu(UM719/Std) <input type="checkbox"/> UM753-1	
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	

Battery Placement:

None Screw

Front Rear None

Foam: Front Rear None

Battery Type

Straight Separate Short

Type: _____

Chassis

F _____ mm **Ride Height:** R _____ mm

Other

Motor: _____

ESC: _____

Pinion/Spur: _____

Truck Condition

- Smooth
- Bumpy
- Low Truction
- Med. Truction
- Higt Truction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- Blue Groore
- Clay
- Dusty
- Other

Wing

- Wing Mount : Narrow Wide
- Wing Angle : 4° 7° 10°
- Blast-S
 - Blast-L
 - Step-S
 - Step-M
 - Step-L
 - Step 2.0
 - Step 3.0
 - Straight
 - Round
- Lip : _____

Tire

	Front	Rear	Traction Compound or comment:
Tire:	_____	_____	_____
Inserts:	_____	_____	_____
Wheel:	_____	_____	_____

Comment
