

Name: _____
 Date: _____
 Track: _____

Track conditions
 Size: Open Med. Tight
 Traction: High Med. Low
 Surface: Smooth Med. Bumpy

Result
 Race time / Lap: _____
 Best lap (1Lap): _____

Front suspension

Rebound stop: _____
 Ride height: _____
 Toe angle: _____
 Kingpin ball spacer: _____
 Lower arm plate: _____
 Anti roll bar: _____
 Upper arm spacer: _____
 Lower arm spacer: _____
 Lower arm position (Kick up): _____

E0160 E2123(Steel) E2161A,B
 E0159 E2124(Steel) E2166(CFRP)
 E2153 E2168(-3)
 E2146 E2147(1.5)
 E0241(2mm)
 E0239 E0240(1mm)
 E0160 E2123(Steel)
 E0159 E2124(Steel)

Kingpin ball spacer: _____
 Upper arm position: _____

Front shocks

Piston: _____ Oil: _____
 Spring: _____
 Shock position: _____
 Pivot ball position: Front Rear

Steering ackerman

Front

Front upper plate

E2148D E2158(CFRP)

Servo saver arm

E2301A E2310(Aluminum)

Rear suspension

Rebound stop: _____
 Ride height: _____
 Camber angle: _____
 Lower arm plate: _____
 Anti roll bar: _____
 Lower arm spacer: _____
 Upright spacer: _____
 Lower arm position: _____

E2131 E2134(Aluminum) E2162A,B
 E0241(2mm) E2167(CFRP)
 E0239 E0240(1mm)

Upper arm position: _____
 Lower arm position: _____

Rear shocks

Piston: _____ Oil: _____
 Spring: _____
 Shock position: _____
 Pivot ball position: Front Rear

Center shaft

E2215,E2216(CVD) E2230,E2231

Tension rod

Front: E2107A(Long) E2107B(Short)
 Rear: E2148C E0803(Rubber)

Weight

Power train

Motor: _____
 ESC: _____
 Battery: _____

Diff. Gear

Oil _____
 Front: _____
 Rear: _____
 Center: 44T 46T

Tires

Front Rear
 Type: _____
 Compound: _____
 Inserts: _____
 Wheel: _____

Pinion gear

12T 13T 14T
 15T 16T 17T
 18T

Body/Wing

Body: _____
 Wing: _____
 Wing stay: E2422A E2428A(+15)
 Wing position: _____

Comments

.....

