

Name: _____ Date: _____ Event: _____

Track: Indoor Outdoor Size: Small Medium Large Traction: Low Med High

Surface: Smooth Bumpy Rutted Type: Loose/Loamy Hard Pack Blue Groove Clay

Bumpsteer/Ackerman/Servo Saver: _____ Condition: Dusty Dry Wet Muddy

washers over # ballstud orientation

washers under # ballstud orientation

front middle rear

Front End:

"A" Block

(0° WITH CENTER DOT INSERT)
Composite Aluminum

(Sweep)

"B" Block

(10° WITH CENTER DOT INSERT)
Composite Aluminum

(Kick Up)

Rear End:

"C" Block

(3° WITH CENTER DOT INSERT)
Composite Aluminum (-1°)

(Anti-Squat)

"D" Block

(3° WITH CENTER DOT INSERT)
Composite Aluminum

(Rear Toe)

Turns from fully tight

of washers

Suspension:

	FRONT	REAR
RIDE HEIGHT		
CAMBER		
CASTER		
SWEEP		
KICK UP		
ANTI-SQUAT		
TOE (in/out)		
SWAY BAR		
SHOCK LENGTH (DROOP)		

Body/Mounts:

BODY MAKE _____

Front (Height)

Rear (Height)

Wheelbase:

large 2mm

small 1mm

mm /FRONT

mm /REAR

Shocks:

	FRONT	REAR
OIL		
BRAND		
PISTON		
SPRING		
REBOUND	%	%
STD/EMUL/VENT		

Tires /Wheels:

	FRONT	REAR
BRAND/TREAD		
COMPOUND		
INSERT		
WHEEL		

NOTES:

Differential Oil:

FRONT	CENTER	REAR

Electronics:

ESC:	
Battery:	
Motor:	
Radio:	
Servo:	

Drivetrain:

PINION SIZE		(teeth)
-------------	--	---------

Chassis Braces:

Front Middle Rear

(front brace is always recommended)

Notes:
